

Ombra

220-240V AC dimmable (DALI/Push DIM)  
A16019.115.0502




Data sheet

|                          |                          |
|--------------------------|--------------------------|
| CODE                     | A16019.115.0502          |
| SYSTEM POWER CONSUMPTION | 23W                      |
| EFFICACY                 | 39.65lm/W                |
| LIGHT SOURCE             | LED                      |
| COLOUR TEMPERATURE       | 2700K Ra>90              |
| POWER SUPPLY             | 220-240V AC              |
| FREQUENCY                | 50/60Hz                  |
| ELECTRICAL CONFIGURATION | dimmable (DALI/Push DIM) |
| DRIVER                   | integrated included      |
| NOMINAL LUMINOUS FLUX    | 2896lm                   |
| LUMEN OUTPUT             | 912lm                    |
| EFFICIENCY               | 31.5%                    |
| WEIGHT                   | 1,17 Kg                  |
| PROTECTION DEGREE        | IP20                     |
| COLOUR TOLLERANCES       | SDCM <3                  |
| PACKING DIMENSIONS       | 0,0 x 0,0 x 0,0 cm       |



Wall-mounted luminaire for indoor installation, with direct emission.  
Extruded aluminium frame with polyacrylic paint finish in mat black or mat brass.  
White PVC-coated woven fabric shade.  
Polycarbonate inner diffuser screen.  
Wall mounting base in pickled sheet metal with polyacrylic paint in satin black or satin brass colour.  
Integrated ballast in the fixing base.

Technical drawing



Polar diagram