


PANZERI

Opuntia

220-240V AC DIM-to-warm + tunable white
P06819.002.9121

 mat brass



Data sheet

CODE	P06819.002.9121
SYSTEM POWER CONSUMPTION	17W
EFFICACY	82.35lm/W
LIGHT SOURCE	LED
COLOUR TEMPERATURE	2200-4000K Ra>90
LIGHT DISTRIBUTION	adjustable
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	DIM-to-warm + tunable white
DRIVER	integrated included
LUMEN OUTPUT	1400lm
WEIGHT	0,00 Kg
PROTECTION DEGREE	IP40
PACKING DIMENSIONS	0,0 x 0,0 x 0,0 cm



Ceiling lighting fixture for interiors, with swivelling light beam.
Pickled sheet metal ceiling bracket in polyacrylic paint.
Pickled sheet metal wall plate in polyacrylic paint.
Turned steel and die-cast aluminium joints in polyacrylic paint.
Structure with adjustable arms in extruded aluminium in white, mat black, bronze, mat brass or titanium polyacrylic paint.
Steel wire rope slings.
Die-cast aluminium heads rotating on two axes in polyacrylic paint.
Modelled polycarbonate diffusers with opaline finish and serigraphy.
Push-button to adjust luminosity and light shade according to 5 levels of visual comfort.

Technical drawing

