


Haul




Milan



HAUL 40 AC SF W.

Ø40 x 85 mm | H. 91 mm

1 x DOB LED 5W 

500 lumens | 2.700K

| CRI 90


3-step MacAdam


PF. 0,95

Dimmable

Class I: Basic insulation

Acabados

6803  Matt white lacquering
(RAL 9016)

6804  Matt black lacquering
(RAL 9005)

DOWNLOADS

Catalogue

[Haul](#)

3D Files

[6803/6804](#)

3D Max Files

[6803/6804](#)

Assembly instructions

[6803/6804](#)

Photometric curve

[6803/6804](#)


Economic efficiency index

[6803/6804](#)

Haul, the distance of light

Cylinder in extruded aluminium. Finishing in matt white lacquer (RAL 9016) and matt black lacquer (RAL 9005). Inner core, with heat sink function and Led housing, injected

in aluminium. Injected polycarbonate reflector with high vacuum aluminium finish. Switch integrated in the wall fixing base.



HAUL 40 AC MF W.

Ø40 x 100 mm | H. 117 mm

1 x DOB LED 5W

500 lumens | 2.700K

| CRI 90

3-step MacAdam

PF. 0,95


Dimmable

Class I: Basic insulation

Finishes

6805 Matt white lacquering (RAL 9016)

6806 Matt black lacquering (RAL 9005)



HAUL 55 AC T1P.

Ø55 x 100 mm | H. 183 mm

1 x DOB LED 7W

665 lumens | 2.700K

CRI 90 | 3-step MacAdam

PF. 0,95 | Dimmable

Class I: Basic insulation

Finishes

6859 Matt white lacquering (RAL 9016)

6860 Matt black lacquering (RAL 9005)

1 x GU10 Bulb retrofit

Led 8W Ø50mm

Code 2123 | CRI 90

700 lumens | 2.700K

Dimmable

Class I: Basic insulation

Finishes

6839 Matt white lacquering (RAL 9016)

6840 Matt black lacquering (RAL 9005)

DOWNLOADS

[Catalogue](#)

[Haul](#)

3D Files

[6805/6806](#)

[6859/6860](#)

[6839/6840](#)

3D Max Files

[6805/6806](#)

[6859/6860](#)

[6839/6840](#)

Assembly instructions

[6805/6806](#)

[6859/6860](#)

[6839/6840](#)

Photometric curve

[6805/6806](#)

[6859/6860](#)

[6839/6840](#)

Economic efficiency index


[6805/6806](#)

[6859/6860](#)

[6839/6840](#)


Cylinder in extruded aluminium. Finishing in matt white lacquer (RAL 9016) and matt black lacquer (RAL 9005). Inner core, with heat sink function and Led housing, injected in aluminium. Injected polycarbonate reflector with high vacuum aluminium finish.

Base where axis is housed for movement, in injected aluminium. Base for fixing to wall or ceiling, injected in zamak. Finishing in matt white lacquer (RAL 9016) and matt black lacquer (RAL 9005). Switch integrated in the wall fixing base.



HAUL 40 AC SF W.

Ø40 x 70 mm | H. 97 mm

1 x DOB LED 5W 

500 lumens | 2.700K

| CRI 90


3-step MacAdam


PF. 0,95

Dimmable

Class I: Basic insulation

Acabados

6813  Matt white lacquering
(RAL 9016)

6814  Matt black lacquering
(RAL 9005)

Cylinder in extruded aluminium. Finishing in matt white lacquer (RAL 9016) and matt black lacquer (RAL 9005). Inner core, with heat sink function and Led housing, injected in aluminium. Injected polycarbonate reflector with high vacuum

aluminium finish. Base where axis is housed for movement, in injected aluminium. Finishing in matt white lacquer (RAL 9016) and matt black lacquer (RAL 9005). Base for fixing in bed head.

DOWNLOADS

Catalogue

[Haul](#)

3D Files

[6813/6814](#)

3D Max Files

[6813/6814](#)

Assembly instructions

[6813/6814](#)

Photometric curve

[6813/6814](#)

Economic efficiency index

[6813/6814](#)