# GlamOrigin

# **GLAMORA**

### 1. Description

GlamOrigin is a three-dimensional textured wallcovering, created with a semi-handcrafted relief process that reinterprets the aesthetics of sculpted concrete. Its composition is the result of layering monocrystalline quartz sands on a non-woven backing. The light mineral residue on the surface and the slight variations in colour are distinctive characteristics, an authentic expression of the use of natural raw materials.

#### 2. Uses

Suitable for interior vertical surfaces in residential, commercial and hospitality environments, GlamOrigin integrates harmoniously in both classic and contemporary spaces, from residential interiors to business and luxury environments. Thanks to the elegance of its textures, it is ideal for defining intimate atmospheres, such as bedrooms, or enhancing shared spaces, such as living rooms. Applied in workplaces or public spaces – restaurants, hotels, showrooms and conference rooms – it gives vertical surfaces a sophisticated and luminous aesthetic.

#### 3. General information

GlamOrigin is a mineral-based wallcovering made from monocrystalline quartz sands. Before applying the product, check that the colour, design, quantity and quality correspond to the item ordered; also make sure you have received the same production batch. The production batch number (Batch n.) is indicated on the label of each roll. Any variations in colour and texture depend on the semi-handcrafted production technique. If variations are found, the purchased material must be returned in its entirety and in its original packaging. Glamora will not accept any claims for cut or applied product.

## 4. Surface preparation

To apply a wallcovering correctly it is essential that you refer to the *Installation Manual*. This can be found inside the box and can also be downloaded from glamora.it from the page entitled Materials. Should you require further details, please contact our Customer Care Service.

Before starting, please make sure that the surface where you will be applying GlamOrigin is perfectly smooth, flat and white. This surface must be completely dry, have a residual humidity level of less than 2.0%, and must be free of any signs of dirt, pencil marks, dust, grit and damp spots. Make sure that there are no drafts in the space where the wallcovering will be applied and that the temperature remains between 15°C and 35°C with no fluctuations.

#### In the presence of a newly-applied top layer of plaster.

Make sure that the base is solid and dry and that there is no mould or rising damp. Apply an extra-fine, white-coloured, smooth skim finish to the entire surface using a suitable cement-based skim coat. To even out absorption and improve adhesion, apply one or two coats of acrylic primer in an aqueous dispersion suitably diluted as recommended by the manufacturer. Wait until this is dry before proceeding to apply GlamOrigin.

#### In the presence of existing plasterwork or a slightly uneven base.

Sand and remove any material that is coming off as well as any salty deposits and old peeling paint. Carefully clean the base using suitable equipment and make sure it is completely dry, even and flat. Apply an extra-fine, white-coloured, smooth skim finish to the entire surface using a suitable cement-based skim coat. To even out absorption and improve adhesion, apply one or two coats of acrylic primer in an aqueous dispersion suitably diluted as recommended by the manufacturer. Wait until this is dry before proceeding to apply GlamOrigin.

#### In the presence of a ceramic wall covering or tiles.

Carefully clean the surface using suitable equipment for ceramic or tiles and remove any traces of limescale. Make sure that the wall is completely dry. Apply a thin, light-coloured, smooth skim finish using a suitable (preferably cement-based) skim coat. Once this is dry, apply a second extra-fine, white-coloured, smooth skim finish using a suitable cement-based skim coat. To even out absorption and improve adhesion, apply one or two coats of acrylic primer in an aqueous dispersion suitably diluted as recommended by the manufacturer. Wait until this is dry before proceeding to apply GlamOrigin.



# 5. Specific instructions for installing the wallcovering

Before applying the wallcovering, use a spray bottle, a sponge or a microfibre cloth to moisten the back of each panel with clean water at room temperature, leaving the material to rest for 10/15 minutes, so as to ensure greater elasticity of the wallcovering during installation. Once you have finished applying the wallcovering, we recommend you use a soft brush to remove any excess quartz from the entire surface.

#### 6. Technical characteristics

DIMENSIONS: Roll width

Roll length Weight

•

Thickness

Pattern

Appearance

Composition

Reaction to fire (UNI EN 13501-1: 2018)

Washability (EN 12956:1999-04 + A1:2002-04)

Colour fastness to light (UNI EN ISO 105-B02:2014)

98 cm | 38.58 in 10 m | 32.80 ft

from 600 to 900 g/m<sup>2</sup> ( $\pm$  10%) from 1.96 to 2.94 oz/sq ft ( $\pm$  10%)

0,9 mm | 0.035 in (± 10%)

Free match:

98/64 cm | 38.58/25.19 in

Three-dimensional sandy texture

Quartz sand 70%

Non-woven fabric 20%

Water-based components 10%

Euro class: B-s1, d0

Spongeability (mark on 5): 5 Washability (mark on 5): 5

viaoriability (mark on o). o

Washable. See instructions in point 6 "Cleaning and care"

Index 6-7

#### 7. Certifications

FSC® TUVDC-COC-100988 TUVDC-CW-100988

Chemical safety certification (EN 15102:2007+A1:2011)

Heavy metals and specific

elements: Passed Formaldehyde: Passed

Analytical Report (EN 12149) Compliant

# 8. Cleaning and care

Before cleaning your wallcovering, it is recommended that you read the manual *Care and Maintenance Advice*, which can be downloaded from the *Materials* page of *glamora.it*. Should you require further details, please contact our Customer Care Service.

GlamOrigin is a spongeable wallcovering that, thanks to its mineral composition and semi-handcrafted manufacturing, requires particular attention when handling. In case of stains, it is essential to act promptly by gently dabbing the surface with a clean sponge moistened with lukewarm water (using the non-abrasive side) or with a damp, lint-free white cloth. It is important to use only clean water, avoiding any type of detergent, and to be careful not to rub the surface excessively. Once cleaning is complete, it is recommended to dry the material thoroughly with a dry, lint-free cloth, to preserve its integrity and appearance.

Glamora is not responsible for any damage caused during cleaning.

# 9. Warnings

- Product for professional use.
- Follow the national regulations.
- Make sure that the surface is perfectly clean, dry and planar.
- If necessary, require the safety data sheet.
- For any information that is not provided, please consult the Glamora assistance service T +39 0536.076.403 contact@glamora.it

The application of Glamora wallcoverings to surfaces other than those specifically indicated in the manuals or in the company's official installation videos (for example wood, laminate, metal, resin or similar materials) or for uses other than that for which the wallcovering was designed (for example installation on the floor, doors, panels, outdoors or in similar environments) does not comply with the manufacturer's instructions. Therefore, in such cases, any warranty issued to the purchaser will be null and void and Glamora Srl will accept no contractual or extra-contractual liability for the same, nor shall it be answerable for any product defects and/or differences in performance detected as a result. In such cases, the product will be considered as having been sold at the risk and peril of the buyer and Glamora Srl will be under no obligation, nor will it be responsible for upholding any warranty.

Without prejudice to the above, and subject to you sharing the relative technical characteristics, Glamora Srl may provide suggestions regarding the treatment of your installation surfaces, but only as a form of mere courtesy and without accepting any liability, upon your request. In the event of you requesting suggestions and/or subsequently passing a purchase order, it will be considered that the parties are aware of the conditions stated above and that you have specifically acknowledged and accepted these.

# **GLAMORA**

Glamora Srl Via Berna, 12/14 41049 Sassuolo (MO) – Italy T. +39 0536 076403 contact@glamora.it glamora.it

Glamora Showroom Via Solferino, 27 20121 Milano – Italy

Edition: april 2025