PANZERI

Jackie


220-240V AC dimmable (Step DIM) C07701.000.0409

Data sheet

CODE	C07701.000.0409
SYSTEM POWER CONSUMPTION	10W
EFFICACY	70.6lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L90 (B10) 50.000h
COLOUR TEMPERATURE	3000K Ra>90
LIGHT DISTRIBUTION	adjustable
BEAM ANGLE	90°
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	dimmable (Step DIM)
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	884lm
LUMEN OUTPUT	706lm
EFFICIENCY	79.9%
WEIGHT	4,10 Kg
PROTECTION DEGREE	IP40
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	25,0 x 119,0 x 6,0 cm



Technical drawing



Polar diagram

Steel wire rope slings.




Table lighting fixture for interiors, with swivelling light beam. Pickled sheet metal bearing base in polyacrylic paint.

Die-cast aluminium head rotating on two axes in polyacrylic paint. Modelled acrylic diffuser with mat finish and double serigraphy. Push-button to adjust luminosity according to 5 levels of visual comfort. Equipped with a 1,6m (63") long power cable with jack connector and adapter plug.

Die-cast aluminium joints in polyacrylic paint.

Extruded aluminium frame in white, black, red, mat brass or titanium polyacrylic paint.





