PANZERI

Tubino Plus

220-240V AC dimmable (Step DIM) C07317.001.0509

Data sheet

CODEC07317.001.0509SYSTEM POWER CONSUMPTION6,5WEFFICACY56.5lm//WLIGHT SOURCELEDLIGHT SOURCE LIFETIMEL70 (B50) 80.000hCOLOUR TEMPERATURE2700K Ra>90LIGHT DISTRIBUTIONadjustablePOWER SUPPLY220-240V ACFREQUENCY50/60HzELECTRICAL CONFIGURATIONdimmable (Step DIM)DRIVERintegrated includedNOMINAL LUMINOUS FLUX475lmLUMEN OUTPUT339lmEFFICIENCY71.4%VEIGHT1.42 KgPROTECTION DEGREEIP20		
EFFICACY56.5lm/WLIGHT SOURCELEDLIGHT SOURCE LIFETIMEL70 (B50) 80.000hCOLOUR TEMPERATURE2700K Ra>90LIGHT DISTRIBUTIONadjustablePOWER SUPPLY220-240V ACFREQUENCY50/60HzELECTRICAL CONFIGURATIONdimmable (Step DIM)DRIVERintegrated includedNOMINAL LUMINOUS FLUX475lmLUMEN OUTPUT339lmEFFICIENCY71.4%WEIGHT1,42 Kg	CODE	C07317.001.0509
LIGHT SOURCELEDLIGHT SOURCE LIFETIMEL70 (B50) 80.000hCOLOUR TEMPERATURE2700K Ra>90LIGHT DISTRIBUTIONadjustablePOWER SUPPLY220-240V ACFREQUENCY50/60HzELECTRICAL CONFIGURATIONdimmable (Step DIM)DRIVERintegrated includedNOMINAL LUMINOUS FLUX475lmLUMEN OUTPUT339lmEFFICIENCY71.4%WEIGHT1,42 Kg	SYSTEM POWER CONSUMPTION	6,5W
LIGHT SOURCE LIFETIMEL70 (B50) 80.000hCOLOUR TEMPERATURE2700K Ra>90LIGHT DISTRIBUTIONadjustablePOWER SUPPLY220-240V ACFREQUENCY50/60HzELECTRICAL CONFIGURATIONdimmable (Step DIM)DRIVERintegrated includedNOMINAL LUMINOUS FLUX475lmLUMEN OUTPUT339lmEFFICIENCY71.4%WEIGHT1,42 Kg	EFFICACY	56.5lm/W
COLOUR TEMPERATURE 2700K Ra>90 LIGHT DISTRIBUTION adjustable POWER SUPPLY 220-240V AC FREQUENCY 50/60Hz ELECTRICAL CONFIGURATION dimmable (Step DIM) DRIVER integrated included NOMINAL LUMINOUS FLUX 475lm LUMEN OUTPUT 339lm EFFICIENCY 71.4% WEIGHT 1,42 Kg	LIGHT SOURCE	LED
LIGHT DISTRIBUTION adjustable POWER SUPPLY 220-240V AC FREQUENCY 50/60Hz ELECTRICAL CONFIGURATION dimmable (Step DIM) DRIVER integrated included NOMINAL LUMINOUS FLUX 475lm LUMEN OUTPUT 339lm EFFICIENCY 71.4% WEIGHT 1,42 Kg	LIGHT SOURCE LIFETIME	L70 (B50) 80.000h
POWER SUPPLY 220-240V AC FREQUENCY 50/60Hz ELECTRICAL CONFIGURATION dimmable (Step DIM) DRIVER integrated included NOMINAL LUMINOUS FLUX 475lm LUMEN OUTPUT 339lm EFFICIENCY 71.4% WEIGHT 1,42 Kg	COLOUR TEMPERATURE	2700K Ra>90
FREQUENCY 50/60Hz ELECTRICAL CONFIGURATION dimmable (Step DIM) DRIVER integrated included NOMINAL LUMINOUS FLUX 475lm LUMEN OUTPUT 339lm EFFICIENCY 71.4% WEIGHT 1,42 Kg	LIGHT DISTRIBUTION	adjustable
ELECTRICAL CONFIGURATION dimmable (Step DIM) DRIVER integrated included NOMINAL LUMINOUS FLUX 475lm LUMEN OUTPUT 339lm EFFICIENCY 71.4% WEIGHT 1,42 Kg	POWER SUPPLY	220-240V AC
DRIVER integrated included NOMINAL LUMINOUS FLUX 475lm LUMEN OUTPUT 339lm EFFICIENCY 71.4% WEIGHT 1,42 Kg	FREQUENCY	50/60Hz
NOMINAL LUMINOUS FLUX 475lm LUMEN OUTPUT 339lm EFFICIENCY 71.4% WEIGHT 1,42 Kg	ELECTRICAL CONFIGURATION	dimmable (Step DIM)
LUMEN OUTPUT 339lm EFFICIENCY 71.4% WEIGHT 1,42 Kg	DRIVER	integrated included
EFFICIENCY 71.4% WEIGHT 1,42 Kg	NOMINAL LUMINOUS FLUX	475lm
WEIGHT 1,42 Kg	LUMEN OUTPUT	339lm
	EFFICIENCY	71.4%
PROTECTION DEGREE IP20	WEIGHT	1,42 Kg
	PROTECTION DEGREE	IP20
COLOUR TOLLERANCES SDCM 3	COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS 10,5 x 60,0 x 15,0 cm	PACKING DIMENSIONS	10,5 x 60,0 x 15,0 cm



Technical drawing










Table lighting fixture for interiors, with swivelling light beam. Die-cast aluminium bearing base in polyacrylic paint. Body in steel tube in champagne, bronze or titanium polyacrylic paint.

Turned brass joint in polyacrylic paint.

Turned aluminium structure in polyacrylic paint. Turned aluminium swivelling head in polyacrylic paint.

Modelled polycarbonate diffuser with opaline finish.

Turned brass end cap in polyacrylic paint.

Push-button to adjust luminosity according to 5 levels of visual comfort.

Equipped with connection cable between the head and the body with fabric covering in champagne (champagne version), bordeaux (bronze version) or green colour (titanium version).

Equipped with a 1,4m (55,1") long power cable with jack connector and adapter plug.

Polar diagram

